



**JUBILANT AGRI & CONSUMER PRODUCTS LIMITED**

**TECHNICAL DATA SHEET**

**JIVANJOR TERMILOK ANTI TERMITE WOOD PRESERVATIVE**

FOR INFORMATION ONLY

JIVANJOR TERMILOK ANTI TERMITE WOOD PRESERVATIVE is an easy to use anti-termite eco-friendly wood preservative. Its advanced anti termite protection formula penetrates deeply into the wood and is highly effective against Termites and Borers and thus helps in increasing life of the wood

**TYPICAL PROPERTIES**

SR No.	CHARACTERISTICS	SPECIFICATIONS
1	Appearance *	Flowing Liquid
2	Drying Time – Surface Dry (approx.)	8 - 10 mins

**APPLICATION METHOD**

• **SURFACE PREPARATION AND APPLICATION**

- Sand the wooden substrate with emery paper no 180 followed by 320 if required. Sanding the surface with emery paper removes contaminants and other surface deformities.
- Clean the wooden substrate with cloth dipped in Termilok.
- Apply Termilok on the wooden substrate with Brush, Spray or Cloth so that the material penetrates well in the wooden surface.
- Increase number of coats in highly infected areas to ensure good protection.

Note: Do not dilute Termilok with any other product as it will reduce the products effectiveness.

**COVERAGE**

- Approximately 12 – 15 Sq. meters. / Litre per coat.

**USPs/ADVANTAGES**

- Prevents attack on wood by Termites and Borers.
- Penetrates deep into the wood to offer good long lasting protection.
- Eco-Friendly easy to apply product.

**AREA OF USAGE**

- Indoor Wooden Surfaces – Solid Wood, Veneer and Plywood.

**PRECAUTIONS**

- Container should be tightly closed after usage. Exposure to air will increase the colour of the material.

**SHELF LIFE**

- 1 Years from Manufacturing Date.

**STORAGE CONDITION**

- Store at 30 +/- 5 Deg C in shaded area away from direct sunlight and heat.

**HEALTH AND SAFETY INFORMATION**

- Please refer to MSDS